

WILLIAMSEN HEAVY DUTY BODIES

IN A FULL RANGE OF SIZES



SMART, DURABLE DESIGN



Specifications for Heavy Duty Bodies

BODY LENGTH	10 FT.	12 FT.	15 FT.	16 FT.	17 FT.	18 FT.
INNER DIMENSION	84"	84"	84"	84"	84"	84"
SIDE HEIGHT	28"	28"	46"	46"	55"	55"
BODY CAPACITY	6 Yards	7.26 Yards	16 Yards	16 Yards	20 Yards	21.5 Yards

Cross-memberless design creates greater torsion resistance against twisting.

LENGTH

10 ft. to 22 ft.

WIDTH

86" I.D. 96" O.D.

Optional widths available upon request.

SIDE CONSTRUCTION

10 gauge 65,000 PSI high strength steel.
Dirt shedding sloped top and bottom rail.
7 gauge rear corner post.

SIDE OPTIONS

7 gauge 65,000 PSI.
¼" 450 HARDOX® 175/225K PSI quench and tempered abrasion resistant steel.
1 to 4 horizontal side braces available.

FRONT

3/16" 65,000 PSI high strength steel.
62" high with 2 horizontal braces.

CYLINDER HOUSING

Inboard or outboard cylinder.

BODY UNDERSTRUCTURE

Barless understructure design with 8" I-beam stringers.

FLOORS

¼" 450 HARDOX® 175/225K PSI quench and tempered high strength steel.
Abrasion resistant steel.
Side floor formed in one piece.

FLOOR OPTIONS

Wood cushion.
Double overlay floor construction.

TAILGATE

10 gauge high tensile steel outer panel.
3/16" high tensile inner panel to form double wall.
Fully boxed perimeter with integral formed horizontal brace. Straight style.
Air operated with over center locking hardware.

TAILGATE OPTIONS

¼" 450 HARDOX® 180/220,000 PSI inner panel
High-lift, double linked tailgate, air or hydraulic.
Water tight tailgate.
Additional horizontal or vertical tailgate braces.
Double link hinges.
Asphalt gates, lever actuated or rotary type.
Slope style.

LIGHTS

LED sealed system.
Complies with DOT and FMVSS108.

COATINGS

Epoxy primed
Urethane Top Coat
Cured at 190°

Options:

LINE-X XTRA premium protection,
Fortified with DuPont™ Kevlar®

CUSTOMIZE YOUR WILLIAMSEN BODY WITH THESE SMART OPTIONS:

- Aluminum and Stainless Steel Bodies
- Air operated folding mud flaps
- Spreader aprons
- Walk Rails
- Ladders
- Grip strut steps with grab handles
- Vertical side braces
- Front corner posts
- Side boards
- Asphalt rear end



**FOR CUSTOM ORDERS PLEASE CALL
TOLL FREE 1.800.828.9847
OR VISIT www.williamsenmfg.com**

1925 West Indiana Avenue · Salt Lake City, Utah 84104
Phone (801) 973-9400 · Fax (801) 973-2838

Distributed by:

