

WILLIAMSEN SUPER DUMP WITH MAXLE TRAILING AXLE

QUALITY FABRICATION AND
MANUFACTURING SINCE 1892



SMART, DURABLE DESIGN



*GET THE MAXIMUM AMOUNT OF PROFIT FROM YOUR
PAYLOAD WITH THE WILLIAMSEN SUPER DUMP
AND MAXLE TRAILING AXLE.*



**WILLIAMSEN
MANUFACTURING**

Smooth air ride suspension trailing axle provides exceptional stability and easy ride.

Maxle system doesn't interfere with loading or dumping while stowed in the up position.

BODY STYLE

Standard straight square or optional elliptical body style.

LENGTH: Up to 21' long.

WIDTH: 102" O.D. standard.

SIDE CONSTRUCTION

1/8" HARDOX® 450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

Integral formed horizontal side stiffeners.

Up to 78" side height.

CYLINDER HOUSING

Inboard or outboard mounted cylinder.

FLOOR CONSTRUCTION

3/16" HARDOX® 450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

TAILGATE

1/8" HARDOX® 450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

Boxed Parameter with double panel.

Integral formed horizontal stiffeners.

12" solid header to prevent racking and misalignment.

Tailgate slopes forward 24 degrees.

Tailgate locks are air operated with over-locking hardware.

ADDITIONAL OPTIONS

- Air operated folding mud flaps.
- Tarp system.
- Spreader chains with concealed mounting.

COATINGS

Epoxy primed
Urethane Top Coat
Cured at 190°

Options:

LINE-X XTRA premium protection,
Fortified with DuPont™ Kevlar®

State axle configurations

This map is to be used as a guideline. Check with your local Department of Transportation for your specific requirements.



KEY:

■ Seven Axle States

■ Six Axle States

■ Four Axle States

■ Check with your local D.O.T.

**SILENT
DRIVE**



**WILLIAMSEN
MANUFACTURING**

FOR CUSTOM ORDERS PLEASE CALL
TOLL FREE 1.800.828.9847
OR VISIT www.williamsenmfg.com

1925 West Indiana Avenue • Salt Lake City, Utah 84104
Phone (801) 973-9400 • Fax (801) 973-2838

Distributed by:

