

WILLIAMSEN HEAVY DUTY SLOPE SIDE BODIES

QUALITY FABRICATION AND
MANUFACTURING SINCE 1892



SMART, DURABLE DESIGN



Trust Williamsen to build your
next dump body.



WILLIAMSEN
MANUFACTURING

Specifications for Heavy Duty Slope Side Bodies

Cross-memberless design creates greater torsion resistance against twisting.

LENGTH

10 ft. to 22 ft.

WIDTH

86" I.D. 96" O.D.

Optional widths available upon request.

SIDE CONSTRUCTION

10 gauge 65,000 PSI high strength steel.
Front side is 55" and slopes to 46" at the rear.
Dirt shedding sloped top and bottom rail.
3 horizontal side stiffeners.
7 gauge rear corner post.

SIDE OPTIONS

7 gauge 65,000 PSI.
1/4" 450 HARDOX® 175/225K PSI quench and tempered abrasion resistant steel.
Front side starting from 55" and tapers to as low as 34" at the rear.
*Multiple options available.

FRONT

3/16" 65,000 PSI high strength steel.
62" high with 2 horizontal braces.

CYLINDER HOUSING

Inboard or outboard cylinder.

BODY UNDERSTRUCTURE OPTIONS

Trapezoidal tubular design
Barless understructure design
with 8" I-beam stringers.

FLOORS

1/4" 450 HARDOX® 175/225K PSI quench and tempered high strength steel.
Abrasion resistant steel.
Side floor formed in one piece.

FLOOR OPTIONS

Wood cushion.
Double overlay floor construction.

TAILGATE

10 gauge high tensile steel outer panel.
3/16" high tensile inner panel to form double wall.
Fully boxed perimeter with integral formed horizontal brace. Straight style.
Air operated with over center locking hardware.

TAILGATE OPTIONS

1/4" 450 HARDOX® 180/220,000 PSI inner panel.
High-lift, double linked tailgate, air or hydraulic.
Water tight tailgate.
Additional horizontal or vertical tailgate braces.
Double link hinges.
Asphalt gates, lever actuated or rotary type.
Slope style.

LIGHTS

LED sealed system.
Complies with DOT and FMVSS108.

CUSTOMIZE YOUR WILLIAMSEN BODY WITH THESE SMART OPTIONS:

- Aluminum and Stainless Steel Bodies
- Air operated folding mud flaps
- Spreader aprons
- Walk Rails
- Ladders
- Grip strut steps with grab handles
- Vertical side braces
- Front corner posts
- Side boards
- Asphalt rear end

COATINGS

Epoxy primed
Urethane Top Coat
Cured at 190°

Options:

LINE-X XTRA premium protection,
Fortified with DuPont™ Kevlar®



FOR CUSTOM ORDERS PLEASE CALL

TOLL FREE 1.800.828.9847

OR VISIT www.williamsenmfg.com

1925 West Indiana Avenue · Salt Lake City, Utah 84104

Phone (801) 973-9400 · Fax (801) 973-2838

Distributed by:

